

Item no.	4286 Same as: 4287, 4288, 4289, 4290, 4291, 4292, 4293, 4294, 4295, 4296, 4297, 4298, 4299, 4300, 4301, 4302, 4303, 4304, 4305, 4306, 4307, 4308, 4309, 4310, 4311, 4312, 4313, 4314, 4315
No. to identify the observations received from the public	Same as: No. 112478/25.08.2006, No. 112379/25.08.2006, No. 112380/25.08.2006, No. 112381/25.08.2006, No. 112382/25.08.2006, No. 112383/25.08.2006, No. 112384/25.08.2006, No. 112385/25.08.2006, No. 112386/25.08.2006, No. 112387/25.08.2006, No. 112388/25.08.2006, No. 112389/25.08.2006, No. 112390/25.08.2006, No. 112391/25.08.2006, No. 112392/25.08.2006, No. 112393/25.08.2006, No. 112394/25.08.2006, No. 112395/25.08.2006, No. 112396/25.08.2006, No. 112397/25.08.2006, No. 112398/25.08.2006, No. 112399/25.08.2006, No. 112500/25.08.2006, No. 112501/25.08.2006, No. 112502/25.08.2006, No. 112503/25.08.2006, No. 112504/25.08.2006, No. 112505/25.08.2006, No. 112506/25.08.2006 No. 112399/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µg/m³ hourly average and 179µg/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4316 Same as: 4317, 4318, 4319, 4320, 4321, 4322, 4323, 4324, 4325, 4326, 4327, 4328, 4329, 4330, 4331, 4332, 4333, 4334, 4335, 4336, 4337, 4338, 4339, 4340, 4341, 4342, 4343, 4344, 4345
No. to identify the observations received from the public	Same as: No. 114089/25.08.2006, No. 114088/25.08.2006, No. 114087/25.08.2006, No. 114086/25.08.2006, No. 114085/25.08.2006, No. 114084/25.08.2006, No. 114083/25.08.2006, No. 113957/25.08.2006, No. 113958/25.08.2006, No. 113959/25.08.2006, No. 113960/25.08.2006, No. 113961/25.08.2006, No. 113962/25.08.2006, No. 113963/25.08.2006, No. 113964/25.08.2006, No. 113965/25.08.2006, No. 113966/25.08.2006, No. 113967/25.08.2006, No. 113968/25.08.2006, No. 113969/25.08.2006/22.09.2006, No. 113970/25.08.2006, No. 113971/25.08.2006, No. 113972/25.08.2006, No. 113973/25.08.2006, No. 113974/25.08.2006, No. 113975/25.08.2006, No. 113976/25.08.2006, No. 113977/25.08.2006, No. 113978/25.08.2006 No. 114090/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4346 Same as: 4347, 4348, 4349, 4350, 4351, 4352, 4353, 4354, 4355, 4356, 4357, 4358, 4359, 4360, 4361, 4362, 4363, 4364, 4365, 4366, 4367, 4368, 4369, 4370, 4371, 4372, 4373, 4374, 4375
No. to identify the observations received from the public	No. 114285/25.08.2006 Same as: No. 114286/25.08.2006, No. 114287/25.08.2006, No. 114288/25.08.2006, No. 114289/25.08.2006, No. 114291/25.08.2006, No. 114292/25.08.2006, No. 114293/25.08.2006, No. 114294/25.08.2006, No. 114295/25.08.2006, No. 114296/25.08.2006, No. 114297/25.08.2006, No. 114298/25.08.2006, No. 114299/25.08.2006, No. 114301/25.08.2006, No. 114302/25.08.2006, No. 114303/25.08.2006, No. 114304/25.08.2006, No. 114305/25.08.2006, No. 114306/25.08.2006, No. 114307/25.08.2006, No. 114308/25.08.2006, No. 114309/25.08.2006, No. 114310/25.08.2006, No. 114311/25.08.2006, No. 114312/25.08.2006, No. 114313/25.08.2006, No. 114314/25.08.2006, No. 114315/25.08.2006, No. 114316/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings pond; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4376 Same as: 4377, 4378, 4379, 4380, 4381, 4382, 4383, 4384, 4385, 4386, 4387, 4388, 4389, 4390, 4391, 4392, 4393, 4394, 4395, 4396, 4397, 4398, 4399, 4400, 4401, 4402, 4403, 4404, 4405
No. to identify the observations received from the public	Same as: No. 113487/25.08.2006, No. 113488/25.08.2006, No. 113489/25.08.2006, No. 113490/25.08.2006, No. 113491/25.08.2006, No. 113492/25.08.2006, No. 113493/25.08.2006, No. 113494/25.08.2006, No. 113495/25.08.2006, No. 113496/25.08.2006, No. 113497/25.08.2006, No. 113498/25.08.2006, No. 113499/25.08.2006, No. 113500/25.08.2006, No. 113501/25.08.2006, No. 113502/25.08.2006, No. 113503/25.08.2006, No. 113504/25.08.2006, No. 113505/25.08.2006, No. 113506/25.08.2006, No. 113507/25.08.2006, No. 113508/25.08.2006, No. 113509/25.08.2006, No. 113513/25.08.2006, No. 113514/25.08.2006, No. 113515/25.08.2006, No. 113516/25.08.2006, No. 113517/25.08.2006, No. 113518/25.08.2006 No. 113486/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4406 Same as: 4407, 4408, 4409, 4410, 4411, 4412, 4413, 4414, 4415, 4416, 4417, 4418, 4419, 4420, 4421, 4422, 4423, 4424, 4425, 4426, 4427, 4428, 4429, 4430, 4431, 4432, 4433, 4434, 4435
No. to identify the observations received from the public	Same as: No. 112508/25.08.2006, No. 112509/25.08.2006, No. 112510/25.08.2006, No. 112511/25.08.2006, No. 112512/25.08.2006, No. 112513/25.08.2006, No. 112514/25.08.2006, No. 112515/25.08.2006/15.09.2006, No. 112516/25.08.2006, No. 112517/25.08.2006, No. 112518/25.08.2006, No. 112519/25.08.2006, No. 112520/25.08.2006, No. 112521/25.08.2006, No. 112522/25.08.2006, No. 112523/25.08.2006, No. 112524/25.08.2006, No. 112525/25.08.2006, No. 112526/25.08.2006, No. 112527/25.08.2006, No. 112528/25.08.2006, No. 112529/25.08.2006, No. 112530/25.08.2006, No. 112531/25.08.2006, No. 112532/25.08.2006, No. 112533/25.08.2006, No. 112534/25.08.2006, No. 112535/25.08.2006, No. 112536/25.08.2006 No. 112507/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4436 Same as: 4437, 4438, 4439, 4440, 4441, 4442, 4443, 4444, 4445, 4446, 4447, 4448, 4449, 4450, 4451, 4452, 4453, 4454, 4455, 4456, 4457, 4458, 4459, 4460, 4461, 4462, 4463, 4464, 4465
No. to identify the observations received from the public	No. 112537/25.08.2006 Same as: No. 112538/25.08.2006, No. 112539/25.08.2006, No. 112540/25.08.2006, No. 112541/25.08.2006, No. 112542/25.08.2006, No. 112543/25.08.2006, No. 112544/25.08.2006, No. 112545/25.08.2006, No. 112546/25.08.2006, No. 112547/25.08.2006, No. 112548/25.08.2006, No. 112549/25.08.2006, No. 112550/25.08.2006, No. 112551/25.08.2006, No. 112552/25.08.2006, No. 112553/25.08.2006, No. 112554/25.08.2006, No. 112555/25.08.2006, No. 112556/25.08.2006, No. 112557/25.08.2006, No. 112558/25.08.2006, No. 112559/25.08.2006, No. 112560/25.08.2006, No. 112561/25.08.2006, No. 112562/25.08.2006, No. 112563/25.08.2006, No. 112564/25.08.2006, No. 112565/25.08.2006, No. 112566/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4466 Same as: 4467, 4468, 4469, 4470, 4471, 4472, 4473, 4474, 4475, 4476, 4477, 4478, 4479, 4480, 4481, 4482, 4483, 4484, 4485, 4486, 4487, 4488, 4489, 4490, 4491, 4492, 4493, 4494, 4495
No. to identify the observations received from the public	No. 112567/25.08.2006 Same as: No. 112568/25.08.2006, No. 112569/25.08.2006, No. 112570/25.08.2006, No. 112571/25.08.2006, No. 112572/25.08.2006, No. 112573/25.08.2006, No. 112574/25.08.2006, No. 112575/25.08.2006, No. 112576/25.08.2006, No. 112577/25.08.2006, No. 112578/25.08.2006, No. 112579/25.08.2006, No. 112580/25.08.2006, No. 112581/25.08.2006, No. 112582/25.08.2006, No. 112583/25.08.2006, No. 112584/25.08.2006, No. 112585/25.08.2006, No. 112586/25.08.2006, No. 112587/25.08.2006, No. 112588/25.08.2006, No. 112589/25.08.2006, No. 112590/25.08.2006, No. 112591/25.08.2006, No. 112592/25.08.2006, No. 112593/25.08.2006, No. 112594/25.08.2006, No. 112595/25.08.2006, No. 112596/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4496 Same as: 4497, 4498, 4499, 4500, 4501, 4502, 4503, 4504, 4505, 4506, 4507, 4508, 4509, 4510, 4511, 4512, 4513, 4514, 4515, 4516, 4517, 4518, 4519, 4520, 4521, 4522, 4523, 4524, 4525
No. to identify the observations received from the public	Same as: No. 113980/25.08.2006, No. 113981/25.08.2006, No. 113982/25.08.2006, No. 113983/25.08.2006, No. 113984/25.08.2006, No. 113985/25.08.2006, No. 113986/25.08.2006, No. 113987/25.08.2006, No. 113988/25.08.2006, No. 113989/25.08.2006, No. 113990/25.08.2006, No. 113991/25.08.2006, No. 113992/25.08.2006, No. 113993/25.08.2006, No. 113994/25.08.2006, No. 113995/25.08.2006, No. 113996/25.08.2006, No. 113997/25.08.2006, No. 113998/25.08.2006, No. 113999/25.08.2006, No. 114000/25.08.2006, No. 114001/25.08.2006, No. 114002/25.08.2006, No. 114003/25.08.2006, No. 114004/25.08.2006, No. 114005/25.08.2006, No. 114006/25.08.2006, No. 114007/25.08.2006, No. 114008/25.08.2006 No. 113979/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding „*the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits*”, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes

from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4526 Same as: 4527, 4528, 4529, 4530, 4531, 4532, 4533, 4534, 4535, 4536, 4537, 4538, 4539, 4540, 4541, 4542, 4543, 4544, 4545, 4546, 4547, 4548, 4549, 4550, 4551, 4552, 4553, 4554, 4555
No. to identify the observations received from the public	No. 113519/25.08.2006 Same as: No. 113520/25.08.2006, No. 113521/25.08.2006, No. 113522/25.08.2006, No. 113523/25.08.2006, No. 113524/25.08.2006, No. 113525/25.08.2006, No. 113526/25.08.2006, No. 113527/25.08.2006, No. 113528/25.08.2006, No. 113529/25.08.2006, No. 113510/25.08.2006, No. 113511/25.08.2006, No. 113512/25.08.2006, No. 113530/25.08.2006, No. 113531/25.08.2006, No. 113532/25.08.2006, No. 113533/25.08.2006, No. 113534/25.08.2006, No. 113535/25.08.2006, No. 113536/25.08.2006, No. 113537/25.08.2006, No. 113538/25.08.2006, No. 113539/25.08.2006, No. 113540/25.08.2006, No. 113541/25.08.2006, No. 113542/25.08.2006, No. 113543/25.08.2006, No. 113544/25.08.2006, No. 113545/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings pond; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4556 Same as: 4557, 4558, 4559, 4560, 4561, 4562, 4563, 4564, 4565, 4566, 4567, 4568, 4569, 4570, 4571, 4572, 4573, 4574, 4575, 4576, 4577, 4578, 4579, 4580, 4581, 4582, 4583, 4584, 4585
No. to identify the observations received from the public	No. 114300/25.08.2006 Same as: No. 114317/25.08.2006, No. 114318/25.08.2006, No. 114319/25.08.2006, No. 114320/25.08.2006, No. 114321/25.08.2006, No. 114322/25.08.2006, No. 114323/25.08.2006, No. 114324/25.08.2006, No. 114325/25.08.2006, No. 114326/25.08.2006, No. 113634/25.08.2006, No. 113635/25.08.2006, No. 113636/25.08.2006, No. 113637/25.08.2006, No. 113638/25.08.2006, No. 113639/25.08.2006, No. 113640/25.08.2006, No. 113641/25.08.2006, No. 113642/25.08.2006, No. 113643/25.08.2006, No. 113644/25.08.2006, No. 113645/25.08.2006, No. 113646/25.08.2006, No. 113647/25.08.2006, No. 113648/25.08.2006, No. 113649/25.08.2006, No. 113650/25.08.2006, No. 113651/25.08.2006, No. 113652/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µg/m³ hourly average and 179µg/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4586 Same as: 4587, 4588, 4589, 4590, 4591, 4592, 4593, 4594, 4595, 4596, 4597, 4598, 4599, 4600, 4601, 4602, 4603, 4604, 4605, 4606, 4607, 4608, 4609, 4610, 4611, 4612, 4613, 4614, 4615
No. to identify the observations received from the public	No. 112597/25.08.2006 Same as: No. 112598/25.08.2006, No. 112599/25.08.2006, No. 112600/25.08.2006, No. 112601/25.08.2006, No. 112602/25.08.2006, No. 112603/25.08.2006, No. 112604/25.08.2006, No. 112605/25.08.2006, No. 112606/25.08.2006, No. 112607/25.08.2006, No. 112608/25.08.2006, No. 112609/25.08.2006, No. 112610/25.08.2006, No. 112611/25.08.2006, No. 112612/25.08.2006, No. 112613/25.08.2006, No. 112614/25.08.2006, No. 112615/25.08.2006, No. 112616/25.08.2006, No. 112617/25.08.2006, No. 112618/25.08.2006, No. 112619/25.08.2006, No. 112620/25.08.2006, No. 112621/25.08.2006, No. 112622/25.08.2006, No. 112623/25.08.2006, No. 112624/25.08.2006, No. 112625/25.08.2006, No. 112626/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µg/m³ hourly average and 179µg/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page 173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4616 Same as: 4617, 4618, 4619, 4620, 4621, 4622, 4623, 4624, 4625, 4626, 4627, 4628, 4629, 4630, 4631, 4632, 4633, 4634, 4635, 4636, 4637, 4638, 4639, 4640, 4641, 4642, 4643, 4644, 4645
No. to identify the observations received from the public	Same as: No. 114010/25.08.2006, No. 114011/25.08.2006, No. 114012/25.08.2006, No. 114013/25.08.2006, No. 114014/25.08.2006, No. 114015/25.08.2006, No. 114016/25.08.2006, No. 114017/25.08.2006, No. 114018/25.08.2006, No. 114019/25.08.2006, No. 114020/25.08.2006, No. 114021/25.08.2006, No. 114022/25.08.2006, No. 114023/25.08.2006, No. 114024/25.08.2006, No. 114025/25.08.2006, No. 114026/25.08.2006, No. 114027/25.08.2006, No. 114028/25.08.2006, No. 114029/25.08.2006, No. 114030/25.08.2006, No. 114031/25.08.2006, No. 114032/25.08.2006, No. 114033/25.08.2006, No. 114034/25.08.2006, No. 114035/25.08.2006, No. 114036/25.08.2006, No. 114037/25.08.2006, No. 114038/25.08.2006 No. 114009/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4646 Same as: 4647, 4648, 4649, 4650, 4651, 4652, 4653, 4654, 4655, 4656, 4657, 4658, 4659, 4660, 4661, 4662, 4663, 4664, 4665, 4666, 4667, 4668, 4669, 4670, 4671, 4672, 4673, 4674, 4675
No. to identify the observations received from the public	No. 113653/25.08.2006 Same as: No. 113654/25.08.2006, No. 113655/25.08.2006, No. 113656/25.08.2006, No. 113657/25.08.2006, No. 113658/25.08.2006, No. 113659/25.08.2006, No. 113660/25.08.2006, No. 113661/25.08.2006, No. 113662/25.08.2006, No. 113663/25.08.2006, No. 113664/25.08.2006, No. 113666/25.08.2006, No. 113667/25.08.2006, No. 113668/25.08.2006, No. 113669/25.08.2006, No. 113670/25.08.2006, No. 113671/25.08.2006, No. 113672/25.08.2006, No. 113673/25.08.2006, No. 113674/25.08.2006, No. 113675/25.08.2006, No. 113676/25.08.2006, No. 113677/25.08.2006, No. 113678/25.08.2006, No. 113679/25.08.2006, No. 113680/25.08.2006, No. 113681/25.08.2006, No. 113682/25.08.2006, No. 113683/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4676 Same as: 4677, 4678, 4679, 4680, 4681, 4682, 4683, 4684, 4685, 4686, 4687, 4688, 4689, 4690, 4691, 4692, 4693, 4694, 4695, 4696, 4697, 4698, 4699, 4700, 4701, 4702, 4703, 4704, 4705
No. to identify the observations received from the public	Same as: No. 113547/25.08.2006, No. 113548/25.08.2006, No. 113549/25.08.2006, No. 113550/25.08.2006, No. 113551/25.08.2006, No. 113552/25.08.2006, No. 113553/25.08.2006, No. 113554/25.08.2006, No. 113555/25.08.2006, No. 113556/25.08.2006, No. 113557/25.08.2006, No. 113558/25.08.2006, No. 113559/25.08.2006, No. 113560/25.08.2006, No. 113561/25.08.2006, No. 113562/25.08.2006, No. 113563/25.08.2006, No. 113564/25.08.2006, No. 113565/25.08.2006, No. 113566/25.08.2006, No. 113567/25.08.2006, No. 113568/25.08.2006, No. 113569/25.08.2006, No. 113570/25.08.2006, No. 113571/25.08.2006, No. 113572/25.08.2006, No. 113573/25.08.2006, No. 113574/25.08.2006, No. 113575/25.08.2006 No. 113546/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit;
- Trust funds;
- Letter of credit;
- Surety bonds;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4706 Same as: 4707, 4708, 4709, 4710, 4711, 4712, 4713, 4714, 4715, 4716, 4717, 4718, 4719, 4720, 4721, 4722, 4723, 4724, 4725, 4726, 4727, 4728, 4729, 4730, 4731, 4732, 4733, 4734, 4735
No. to identify the observations received from the public	No. 112627/25.08.2006 Same as: No. 112628/25.08.2006, No. 112629/25.08.2006, No. 112630/25.08.2006, No. 112631/25.08.2006, No. 112632/25.08.2006, No. 112633/25.08.2006, No. 112634/25.08.2006, No. 112635/25.08.2006, No. 112636/25.08.2006, No. 112637/25.08.2006, No. 112638/25.08.2006, No. 112639/25.08.2006, No. 112640/25.08.2006, No. 112641/25.08.2006, No. 1126342/25.08.2006, No. 112643/25.08.2006, No. 112644/25.08.2006, No. 112645/25.08.2006, No. 112646/25.08.2006, No. 112647/25.08.2006, No. 112648/25.08.2006, No. 112649/25.08.2006, No. 112650/25.08.2006, No. 112651/25.08.2006, No. 112652/25.08.2006, No. 112653/25.08.2006, No. 112654/25.08.2006, No. 112655/25.08.2006, No. 112656/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4736 Same as: 4737, 4738, 4739, 4740, 4741, 4742, 4743, 4744, 4745, 4746, 4747, 4748, 4749, 4750, 4751, 4752, 4753, 4754, 4755, 4756, 4757, 4758, 4759, 4760, 4761, 4762, 4763, 4764, 4765
No. to identify the observations received from the public	No. 113576/25.08.2006 Same as: No. 113577/25.08.2006, No. 113578/25.08.2006, No. 113579/25.08.2006, No. 113580/25.08.2006, No. 113581/25.08.2006, No. 113582/25.08.2006, No. 113583/25.08.2006, No. 113584/25.08.2006, No. 113585/25.08.2006, No. 113124/25.08.2006, No. 113125/25.08.2006, No. 113126/25.08.2006, No. 113127/25.08.2006, No. 113128/25.08.2006, No. 113129/25.08.2006, No. 113130/25.08.2006, No. 113131/25.08.2006, No. 113132/25.08.2006, No. 113133/25.08.2006, No. 113134/25.08.2006, No. 113135/25.08.2006, No. 113136/25.08.2006, No. 113137/25.08.2006, No. 113138/25.08.2006, No. 113139/25.08.2006, No. 113140/25.08.2006, No. 113141/25.08.2006, No. 113142/25.08.2006, No. 113143/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µg/m³ hourly average and 179µg/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4766 Same as: 4767, 4768, 4769, 4770, 4771, 4772, 4773, 4774, 4775, 4776, 4777, 4778, 4779, 4780, 4781, 4782, 4783, 4784, 4785, 4786, 4787, 4788, 4789, 4790, 4791, 4792, 4793, 4794, 4795
No. to identify the observations received from the public	No. 113684/25.08.2006 Same as: No. 113685/25.08.2006, No. 113686/25.08.2006, No. 113687/25.08.2006, No. 113688/25.08.2006, No. 113689/25.08.2006, No. 113690/25.08.2006, No. 113691/25.08.2006, No. 113692/25.08.2006, No. 113693/25.08.2006, No. 113694/25.08.2006, No. 113695/25.08.2006, No. 113696/25.08.2006, No. 113697/25.08.2006, No. 113665/25.08.2006, No. 113698/25.08.2006, No. 113699/25.08.2006, No. 113700/25.08.2006, No. 113701/25.08.2006, No. 113702/25.08.2006, No. 113703/25.08.2006, No. 113704/25.08.2006, No. 113705/25.08.2006, No. 113706/25.08.2006, No. 113707/25.08.2006, No. 113708/25.08.2006, No. 113709/25.08.2006, No. 113710/25.08.2006, No. 113711/25.08.2006, No. 113712/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4796 Same as: 4797, 4798, 4799, 4800, 4801, 4802, 4803, 4804, 4805, 4806, 4807, 4808, 4809, 4810, 4811, 4812, 4813, 4814, 4815, 4816, 4817, 4818, 4819, 4820, 4821, 4822, 4823, 4824, 4825
No. to identify the observations received from the public	No. 114039/25.08.2006 Same as: No. 114040/25.08.2006, No. 114041/25.08.2006, No. 114042/25.08.2006, No. 114043/25.08.2006, No. 114044/25.08.2006, No. 114045/25.08.2006, No. 114046/25.08.2006, No. 114047/25.08.2006, No. 114048/25.08.2006, No. 114049/25.08.2006, No. 114050/25.08.2006, No. 114051/25.08.2006, No. 114052/25.08.2006, No. 114053/25.08.2006, No. 114054/25.08.2006, No. 114055/25.08.2006, No. 114056/25.08.2006, No. 114057/25.08.2006, No. 114058/25.08.2006, No. 114059/25.08.2006, No. 114060/25.08.2006, No. 114061/25.08.2006, No. 114062/25.08.2006, No. 114063/25.08.2006, No. 114064/25.08.2006, No. 114065/25.08.2006, No. 114066/25.08.2006, No. 114067/25.08.2006, No. 114068/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4826 Same as: 4827, 4828, 4829, 4830, 4831, 4832, 4833, 4834, 4835, 4836, 4837, 4838, 4839, 4840, 4841, 4842, 4843, 4844, 4845, 4846, 4847, 4848, 4849, 4850, 4851, 4852, 4853, 4854, 4855
No. to identify the observations received from the public	Same as: No. 113714/25.08.2006, No. 113715/25.08.2006, No. 113716/25.08.2006, No. 113717/25.08.2006, No. 113718/25.08.2006, No. 113719/25.08.2006, No. 113720/25.08.2006, No. 113721/25.09.2006, No. 113722/25.08.2006, No. 113723/25.08.2006, No. 113724/25.08.2006, No. 113725/25.08.2006, No. 113726/25.08.2006, No. 113727/25.08.2006, No. 113728/25.08.2006, No. 113729/25.08.2006, No. 113730/25.08.2006, No. 113731/25.08.2006, No. 113732/25.08.2006, No. 113733/25.08.2006, No. 113734/25.08.2006, No. 113735/25.08.2006, No. 113736/25.08.2006, No. 113737/25.08.2006, No. 113738/25.08.2006, No. 113738/25.08.2006, No. 113739/25.08.2006, No. 113740/25.08.2006, No. 113741/25.08.2006 No. 113713/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4856 Same as: 4857, 4858, 4859, 4860, 4861, 4862, 4863, 4864, 4865, 4866, 4867, 4868, 4869, 4870, 4871, 4872, 4873, 4874, 4875, 4876, 4877, 4878, 4879, 4880, 4881, 4882, 4883, 4884, 4885
No. to identify the observations received from the public	No. 113144/25.08.2006 Same as: No. 113145/25.08.2006, No. 113146/25.08.2006, No. 113147/25.08.2006, No. 113148/25.08.2006, No. 113149/25.08.2006, No. 113150/25.08.2006, No. 113151/25.08.2006, No. 113152/25.08.2006, No. 113153/25.08.2006, No. 113154/25.08.2006, No. 113155/25.08.2006, No. 113156/25.08.2006, No. 113157/25.08.2006, No. 113158/25.08.2006, No. 113159/25.08.2006, No. 113160/25.08.2006, No. 113161/25.08.2006, No. 113162/25.08.2006, No. 113163/25.08.2006, No. 113164/25.08.2006, No. 113165/25.08.2006, No. 113166/25.08.2006, No. 113167/25.08.2006, No. 113168/25.08.2006, No. 113169/25.08.2006, No. 113170/25.08.2006, No. 113171/25.08.2006, No. 113172/25.08.2006, No. 113173/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4886 Same as: 4887, 4888, 4889, 4890, 4891, 4892, 4893, 4894, 4895, 4896, 4897, 4898, 4899, 4900, 4901, 4902, 4903, 4904, 4905, 4906, 4907, 4908, 4909, 4910, 4911, 4912, 4913, 4914, 4915
No. to identify the observations received from the public	No. 112657/25.08.2006 Same as: No. 112658/25.08.2006, No. 112659/25.08.2006, No. 112660/25.08.2006, No. 112661/25.08.2006, No. 112662/25.08.2006, No. 112663/25.08.2006, No. 112664/25.08.2006, No. 112665/25.08.2006, No. 112666/25.08.2006, No. 112667/25.08.2006, No. 112668/25.08.2006, No. 112669/25.08.2006, No. 112670/25.08.2006, No. 112671/25.08.2006, No. 112672/25.08.2006, No. 112673/25.08.2006, No. 112674/25.08.2006, No. 112675/25.08.2006, No. 112676/25.08.2006, No. 112677/25.08.2006, No. 112678/25.08.2006, No. 112679/25.08.2006, No. 112680/25.08.2006, No. 112681/25.08.2006, No. 112682/25.08.2006, No. 112683/25.08.2006, No. 112684/25.08.2006, No. 112685/25.08.2006, No. 112686/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4916 Same as: 4917, 4918, 4919, 4920, 4921, 4922, 4923, 4924, 4925, 4926, 4927, 4928, 4929, 4930, 4931, 4932, 4933, 4934, 4935, 4936, 4937, 4938, 4939, 4940, 4941, 4942, 4943, 4944, 4945
No. to identify the observations received from the public	Same as: No. 114070/25.08.2006, No. 114071/25.08.2006, No. 114072/25.08.2006, No. 114073/25.08.2006, No. 114074/25.08.2006, No. 114075/25.08.2006, No. 114076/25.08.2006, No. 114077/25.08.2006, No. 114078/25.08.2006, No. 114079/25.08.2006, No. 114080/25.08.2006, No. 114081/25.08.2006, No. 114082/25.08.2006, No. 113376/25.08.2006, No. 113377/25.08.2006, No. 113378/25.08.2006, No. 113379/25.08.2006, No. 113380/25.08.2006, No. 113381/25.08.2006, No. 113382/25.08.2006, No. 113383/25.08.2006, No. 113384/25.08.2006, No. 113375/25.08.2006, No. 113385/25.08.2006, No. 113386/25.08.2006, No. 113387/25.08.2006, No. 113388/25.08.2006, No. 113389/25.08.2006, No. 113390/25.08.2006 No. 114069/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4946 Same as: 4947, 4948, 4949, 4950, 4951, 4952, 4953, 4954, 4955, 4956, 4957, 4958, 4959, 4960, 4961, 4962, 4963, 4964, 4965, 4966, 4967, 4968, 4969, 4970, 4971, 4972, 4973, 4974, 4975
No. to identify the observations received from the public	No. 113743/ 25.08.2006 Same as: No. 113744/25.08.2006, No. 113745/25.08.2006, No. 113746/25.08.2006, No. 113747/25.08.2006, No. 113748/25.08.2006, No. 113749/25.08.2006, No. 113750/25.08.2006, No. 113752/25.08.2006, No. 113753/25.08.2006, No. 113754/25.08.2006, No. 113755/25.08.2006, No. 113756/25.08.2006, No. 113757/25.08.2006, No. 113758/25.08.2006, No. 113759/25.08.2006, No. 113760/25.08.2006, No. 113761/25.08.2006, No. 113762/25.08.2006, No. 113763/25.08.2006, No. 113764/25.08.2006, No. 113765/25.08.2006, No. 113766/25.08.2006, No. 113767/25.08.2006, No. 113768/25.08.2006, No. 113769/25.08.2006, No. 113770/25.08.2006, No. 113771/25.08.2006, No. 113772/25.08.2006, No. 113773/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roșia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roșia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	4976 Same as: 4977, 4978, 4979, 4980, 4981, 4982, 4983, 4984, 4985, 4986, 4987, 4988, 4989, 4990, 4991, 4992, 4993, 4994, 4995, 4996, 4997, 4998, 4999, 5000, 5001, 5002, 5003, 5004, 5005
No. to identify the observations received from the public	No. 112687/25.08.2006 Same as: No. 112688/25.08.2006, No. 112689/25.08.2006, No. 112690/25.08.2006, No. 112691/25.08.2006, No. 112692/25.08.2006, No. 112693/25.08.2006, No. 112694/25.08.2006, No. 112695/25.08.2006, No. 112696/25.08.2006, No. 112697/25.08.2006, No. 112698/25.08.2006, No. 112699/25.08.2006, No. 112700/25.08.2006, No. 112701/25.08.2006, No. 112702/25.08.2006, No. 112703/25.08.2006, No. 112704/25.08.2006, No. 112705/25.08.2006, No. 112706/25.08.2006, No. 112707/25.08.2006/18.09.2006, No. 112708/25.08.2006, No. 112709/25.08.2006, No. 112710/25.08.2006, No. 112711/25.08.2006, No. 167712/18.09.2006, No. 112713/25.08.2006, No. 112714/25.08.2006, No. 112715/25.08.2006, No. 112716/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corma Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	5006 Same as: 5007, 5008, 5009, 5010, 5011, 5012, 5013, 5014, 5015, 5016, 5017, 5018, 5019, 5020, 5021, 5022, 5023, 5024, 5025, 5026, 5027, 5028, 5029, 5030, 5031, 5032, 5033, 5034, 5035
No. to identify the observations received from the public	No. 113174/25.08.2006 Same as: No. 113175/25.08.2006, No. 113176/25.08.2006, No. 113177/25.08.2006, No. 113178/25.08.2006, No. 113179/25.08.2006, No. 113180/25.08.2006, No. 113181/25.08.2006, No. 113182/25.08.2006, No. 113183/25.08.2006, No. 113184/25.08.2006, No. 113185/25.08.2006, No. 113186/25.08.2006, No. 113187/25.08.2006, No. 113188/25.08.2006, No. 113189/25.08.2006, No. 113190/25.08.2006, No. 113191/25.08.2006, No. 113192/25.08.2006, No. 113193/25.08.2006, No. 113194/25.08.2006, No. 113195/25.08.2006, No. 113196/25.08.2006, No. 113197/25.08.2006, No. 113198/25.08.2006, No. 113199/25.08.2006, No. 113200/25.08.2006, No. 113201/25.08.2006, No. 113202/25.08.2006, No. 113203/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	5036 Same as: 5037, 5038, 5039, 5040, 5041, 5042, 5043, 5044, 5045, 5046, 5047, 5048, 5049, 5050, 5051, 5052, 5053, 5054, 5055, 5056, 5057, 5058, 5059, 5060, 5061, 5062, 5063, 5064, 5065
No. to identify the observations received from the public	No. 113774/25.08.2006 Same as: No. 113775/25.08.2006, No. 113776/25.08.2006, No. 113777/25.08.2006, No. 113778/25.08.2006, No. 113779/25.08.2006, No. 113780/25.08.2006, No. 113781/25.08.2006, No. 114355/25.08.2006, No. 114356/25.08.2006, No. 114357/25.08.2006, No. 114358/25.08.2006, No. 114359/25.08.2006, No. 114360/25.08.2006, No. 114361/25.08.2006, No. 114362/25.08.2006, No. 114363/25.08.2006, No. 114364/25.08.2006, No. 114365/25.08.2006, No. 114366/25.08.2006, No. 114367/25.08.2006, No. 114368/25.08.2006, No. 114369/25.08.2006, No. 114370/25.08.2006, No. 114371/25.08.2006, No. 114372/25.08.2006, No. 114373/25.08.2006, No. 114374/25.08.2006, No. 114375/25.08.2006, No. 114376/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abrud-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.

Item no.	5066 Same as: 5067, 5068, 5069, 5070, 5071, 5072, 5073, 5074, 5075, 5076, 5077, 5078, 5079, 5080, 5081, 5082, 5083, 5084, 5085, 5086, 5087, 5088, 5089, 5090, 5091, 5092, 5093, 5094, 5095
No. to identify the observations received from the public	No. 113391/25.08.2006 Same as: No. 113392/25.08.2006, No. 113393/25.08.2006, No. 113394/25.08.2006, No. 113395/25.08.2006, No. 113396/25.08.2006, No. 113397/25.08.2006, No. 113398/25.08.2006, No. 113399/25.08.2006, No. 113400/25.08.2006, No. 113401/25.08.2006, No. 113402/25.08.2006, No. 113403/25.08.2006, No. 113404/25.08.2006, No. 113405/25.08.2006, No. 113406/25.08.2006, No. 113407/25.08.2006, No. 113408/25.08.2006, No. 113409/25.08.2006, No. 113410/25.08.2006, No. 113411/25.08.2006, No. 113412/25.08.2006, No. 113413/25.08.2006, No. 113414/25.08.2006, No. 113415/25.08.2006, No. 113416/25.08.2006, No. 113417/25.08.2006, No. 113418/25.08.2006, No. 113419/25.08.2006, No. 113420/25.08.2006
Proposal	<p>The questioner doesn't agree with the development of the Roşia Montană project and makes the following observations and comments:</p> <ul style="list-style-type: none"> -In EIA there are not presented all the possible risks caused by this project to the protected flora and fauna; -There is no liner proposed for the tailings management facilities; -The proposed waste deposits will be not constructed in conformity with the Romanian legislation in force (at least 1000 m towards the inhabited areas); -Financial guarantees for the closure and post-closure periods were not fixed. <p>SEE THE CONTENT OF THE TYPE 5 CONTESTATION</p>
Solution	<p>It is the nature of risk that it can be mitigated and diminished; it cannot be made to disappear. In order to put this into context, the common action of walking on the street or developing everyday activities have an accident potential. This accident potential is twice higher than within the framework of industrial activities that use hazardous substances.</p> <p>A major chapter of the EIA report was dedicated to the identification of risks for the project. In addition, this chapter provides a discussion of the mitigation measures for each risk and how they were incorporated into the project designs. It is recognized that risk identification is difficult due to the number and diversity of events that can be envisioned. The EIA report cannot assume to cover all of the potential risks associated with the project. However, it has attempted to identify and address the most relevant risks. The extent of risk assessment and the intensity of the prevention and mitigation measures should be proportional to the risk involved and therefore only the risks that have been considered important have been assessed in detail. Each is described below.</p> <p>In the larger sense, the entire EIA report is focused on the assessment of impacts and their associated mitigation. Specifically, Chapter 4 of the EIA presents that impact assessment of the project. The following discussion presents a summary of the impact discussed in the EIA.</p> <p>As far as natural and technological risks assessments are concerned, Chapter 7, "Risk Cases", from the Report on Environmental Impact Assessment, emphasizes the fact that safety and prevention measures, the implementation of the environmental management and risk systems are mitigating the consequences to acceptable levels as compared to the most restrictive norms, standards, the best practices or national and international recommendations in the field. The risk level has been established as moderate and so, socially acceptable. The extension of the risk assessment and the intensity of the prevention and mitigation measures of the consequences should be proportionate to the risk involved. Selection of a specific mitigation technique is depends on the analyzed accident scenario.</p> <p>More detailed assessments are conducted for accident scenarios that, based on the qualitative assessment are found to be potentially major, of probability more than 10^{-6} (reduced recovery periods of 1/1,000,000) meaning that they could have major consequences therefore, elevated associated risk, a higher risk level than 9 to 12 (on a scale of 1-25). To put this in context, simply living in southern Florida rates a 25 on the risk scale.</p> <p>A global assessment of the risks associated with the Roşia Montană Project is obtained by the quick environmental and health risk assessment methodology initially developed by the Italian Ministry of the</p>

Environment and the World Health Organization. Natural hazard and risk identification and analysis presents key data and information in assessing potential technological accidents. Thus:

- In designing the Tailings Management Facility, the design parameters were chosen to fully cover the characteristic seismic risk of the area. These seismic design parameters adopted for the TMF and other facilities on the proposed site result in a safety factor much greater than the minimum accepted under the Romanian and European design standards for such facilities;

- in the sector physically impacted by the Project, the risk of floods will remain very low due to the small catchments (controlled by the Roşia and Corna Streams) the area affected by the operation, and the creation of containment, diversion and drainage hydro-technical structures for storm waters on the site, and in the Abrud catchment in general;

- risks caused by meteorological events have been reviewed and used in assessing the hazards of the affected technological processes.

From the analysis of morphometrical parameters and their correlation with other sets of information on the natural slopes on and near the site shows that the (qualitatively estimated) landslide occurrence risk is low to moderate and its consequences will not cause major impacts on the structural components of the Project.

There is no significant risk associated with resource depletion. Mining activities are planned judiciously, so as to extract only the profitable gold and silver resources and only the necessary construction rock for the Project. The management of the mining concession site will minimize reserve "sterilization" (limitation of future access to the reserves).

In assessing technological hazards and risks, the quantity of hazardous substances on the site was calculated as a total and by category, as provided by the *Notification Procedure* approved by Ministry of Agriculture, Forestry, Water and Environment (MAFWE) Order 1084/2003. Based on an evaluation of hazardous substances in stock on the Project site in relation to the relevant quantities provided by the Government Decision 95/2003 which transposes the Seveso Directive, the Project ranges between the upper and the lower limits, and therefore S.C. Roşia Montană Gold Corporation S.A. is required to prepare a Report on Environmental Impact Assessment Study to be sent to the local environmental authority and the local civilian protection authority a *Safety Report* on its operations to prevent major accident risks.

In assessing the consequences of major accidents involving dangerous substances, physical-mathematical models accepted internationally and especially at EU level, and the current version of the SLAB (Canada) software have been used, the latter for the atmospheric dispersion of denser than air gases, that may handle a multitude of situations and scenarios. Similarly, the EFFECTSGis 5.5 (Netherlands) software, developed for the analysis of the effects of industrial accidents and of consequences. Several scenarios were considered in response to the internal legislative requirements, especially related to the implementation of the Internal Emergency Plans (GD 647/2005). The conclusions of the risk assessment for major accidents were:

- The total destruction of plant facilities may only be caused by terrorist attack with classic or nuclear weapons. Simultaneous damage to the HCl tank (including containment) and to the NaCN solution tank, the tanks containing enriched solution, to one or more leaching tanks, having as a result HCN dispersion into the air. At the same time, under certain situations and weather conditions unfavorable for dispersion, people within 40 m of the emission source, surprised by the toxic cloud for more than 1 minute without respiratory protection equipment, will most certainly die. It may also be considered that, on a radius of about 310 m, persons exposed for more than 10 minutes may suffer serious intoxications that may also lead to death. Toxic effects may occur in persons up to about 2 km downwind of the process plant;

- Operating errors and/or failures in the measurement and control devices, resulting in a lower pH in the leaching tank, thickener and/or DETOX slurry and accidental emissions of hydrocyanic acid. The area affected by concentrations of 290 ppm over a 10 min exposure time is within a circle of 36 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 157.5 m radius. The center of these circles is the middle of the CIL tanks platform;

- Accidental HCN emission from the decanter. The accident may be caused by a drop of pH in the CIL tanks combined with an overdose of flocculent solution and faulty pH monitoring systems. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 65 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 104 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Accidental HCN emission from the DETOX facility. The accident may be caused by a drop of pH in the reactors generated by an overdose of metabisulfite solution and/or copper sulphate combined with faulty pH monitoring systems. The area affected by high 1900 ppm concentrations for a 1 min exposure time is located within a 10 m radius circle. The area affected by concentrations of 300 ppm over a 10 min exposure time is within a circle of 27 m radius and the 50 ppm IDLH threshold for 30 min exposure will be reached over an area of 33 m radius. The center of these circles is mid-distance between the two DETOX facilities;

- Explosion of the LPG storage tank. The LPG storage tank has a 50 ton capacity and is located outdoors, near the heating plant. The simulation was conducted for the worst case scenario, considering an explosion of the full tank. Threshold I with heat 12.5 kW/m² is within a 10.5 m radius circle and Threshold II, of heat radiation 5 kW/m² is within a circle of 15 m radius;

- Damage and/or fire at the fuel tanks. Simulations were conducted for the worst case scenarios, considering ignition and combustion of all the diesel (fire in the tank, or in the containment vat, when full of diesel);

- Corna Dam break and breach development. Two credible accident scenarios were considered in simulating tailings flow out of the Tailings Management Facility, and six credible scenarios for the flow of decant water and tailings pore water, with significant effects on the terrestrial and aquatic ecosystems, in different weather conditions;

- Tailings flow may occur along Corna Valley, on a 800 m (starter dam break) or over 1600 m reach should the Corna dam break in its final stage;

- In regard to water quality impacts, cyanide concentrations in the water in the shape of a pollution plume may reach Arad, near the Romanian-Hungarian border on the Mureş River, in concentrations ranging between 0.03 and 0.5 mg/L. Due to inherent mathematical limitations in the models, these values and the accident effects are considered overestimated. Therefore, the results describe the “worst case scenario” based on extreme dam break assumptions for the Corna Dam.

A new and much more precise and realistic simulation has been subsequently established based on the INCA Mine model, that considers the dispersion, volatilization and breakdown of cyanides during the downstream movement of the pollutant flow (Whiteland et al., 2006).

The model used is the INCA model developed over the past 10 years to simulate both terrestrial and aquatic systems within the EUROLIMPACS EU research program (www.eurolimpacs.ucl.ac.uk). The model has been used to assess the impacts from future mining, and collection and treatment operations for pollution from past mining at Roşia Montană.

The modeling created for Roşia Montană simulates eight metals (cadmium, lead, zinc, mercury, arsenic, copper, chromium, manganese) as well as Cyanide, Nitrate, Ammonia and dissolved oxygen. The model has been applied to the upper catchments at Roşia Montană as well as the complete Abruđ-Arieş-Mureş river system down to the Hungarian Border and on into the Tisa River. The model takes into account the dilution, mixing and physical-chemical processes affecting metals, ammonia and cyanide in the river system and gives estimates of concentrations at key locations along the river, including at the Hungarian Boarder and in the Tisa after the Mureş joins it.

Because of dilution and dispersion in the river system, and of the initial EU BAT-compliant technology adopted for the project (for example, the use of a cyanide destruct process for tailings effluent that reduces cyanide concentration in effluent stored in the TMF to below 6 mg/l), even a large scale unprogrammed release of tailings materials (for example, following failure of the dam) into the river system would not result in transboundary pollution. The model has shown that under worse case dam failure scenario all legal limits for cyanide and heavy metals concentrations would be met in the river water before it crosses into Hungary.

The INCA model has also been used to evaluate the beneficial impacts of the existing mine water collection and treatment and it has shown that substantial improvements in water quality are achieved along the river system under normal operational conditions.

For more information, an information sheet presenting the INCA modeling work is presented under the title of the Mureş River Modeling Program and the full modeling report is presented in Annex 5.1:

- Development of HCN on the tailings pond surface. Simulated emissions of HCN from the Tailings Management Facility pond surface and of their dispersion into the ambient air show that the level

of 400µ g/m³ hourly average and 179µ g/m³ 8hr average will not be exceeded. These HCN concentrations are only slightly over the odor threshold (0.17ppm) and much below potentially dangerous concentrations;

- Cetate Dam break and breach development. Flood modeling was in case of a break in Cetate dam was based on the design parameters obtained from the hydrometeorological study "Assessment of rainfall intensity, frequency and runoff for the Roşia Montană Project - Radu Drobot". The breach characteristics were predicted using the BREACH model, and the maximum height of the flood wave in various flow sections was modeled using the FLDWAV software. The assumptions included a total 800000 m³ discharge for one hour, when the peak of the flood hydrograph is about 4.9 m above base flow immediately below the dam and in the narrow Abrud valley 5.9-7,5 km downstream of the dam, while in the last section considered (10,5 km) water depth is about 2.3 m above base flow and the maximum flow rate 877 m³/s. Further, the broader Aries valley allows the flood wave to propagate on a significantly wider bed, which results in a highly attenuated hydrograph. These results describe the "worst case scenario" based on extreme dam break assumptions:

- Accidents during cyanide transportation. Due to the large quantities of cyanide transported (about 30t /day) the risks associated to this activity were assessed in detail using the ZHA- Zurich Hazard Analysis method. As a consequence, the optimum transport route was selected from the manufacturer to the Process Plant, e.g.;

- Cyanide transport (in solid state) will exclusively involve special SLS (Solid to Liquid System) containers, 16 tons each. The ISO compliant container will be protected by a framework with legs, which allows separation from the transport trailer for temporary storage. The wall is 5.17 mm thick, which, together with the protective framework, provides additional protection to the load in case of accident. This system is considered BAT and is currently one of the safest cyanide transportation options.

It is being mentioned the fact that the study develops the occurrence possibility of these scenarios (pages 166-171, Conclusions).

As regards the cyanides management, there is a baseline study named "Roşia Montană Golden Project, Cyanides Management Plan" prepared in compliance with the "International Management Code for the Manufacture, Transport and Use of Cyanide in the Production of Gold (International Cyanide management Institute) May 2002". S.C. Roşia Montană Gold Corporation is signatory to this code.

Bibliographical references for Chapter 7 "Risk Cases" are listed at page173-176.

*

The impact on protected flora and fauna will exist only locally, but this impact will not lead to the loss of any specie. The Project has been designed even from the beginning to fully comply with the requirements and norms imposed by Romanian and European environmental legislation.

The company believes the fact that the project impact on environment remains significant, especially because covers previous impacts. But, the investments required to ecologically restore/rehabilitate Roşia Montană area in order to address current complex environmental issues, are only achievable following the implementation of some economic projects that will generate and warrant implementation of some direct and responsible actions as a component of base principles of sustainable development concepts. Clean processes and technologies may be developed only in the presence of a solid economic environment fully compliant with the environment that will also resolve previous impacts of anthropic activities.

The base documents of the Project are in fact an unbiased reason of its implementation, considering the highly complex environmental commitment within Roşia Montană area.

Some of the Roşia Montană species that are under a certain protection status stand for an insignificant percentage of the scale of populations estimated at national level. The characterization of species from their habitat point of view exists in the species tables presented in the Biodiversity Chapter of the EIA Report and its annexes, although this is not a requirement imposed by the Habitats Directive. Due to their large volume of information, the annexes of chapter 4.6 Biodiversity can be found in the electronic version of the EIA disclosed by the company both in Romanian and English through approx. 6,000 DVD/CD copies, being accessible on the company website, and on the websites of Ministry of Environment and Water Management, local and regional environmental protection agencies of Alba, Sibiu, Cluj, etc.

From practical point of view, the low value of conservation of the impact area is also indirectly emphasized by the fact that there is no proposal to designate the area a SPA (aviafaunistic special protected area) and by the denial as unfounded of the proposal to designate the area as a pSCI area (sites of community importance).

Taking all these into account, we believe that the proposed Project is compliant with the provisions of EU Directive no. 92/43 Habitats[1], and EU Directive no. 79/409 Birds[2] respectively, especially because within Biodiversity Management Plan, Plan H, several active and responsible measures are provided to reconstruct/rehabilitate several natural habitats, pursuant to the provisions of the same documents [3].

References:

[1] art.3, 2nd paragraph, Each Member State shall contribute to the creation of Natura 2000 (network) in proportion to the representation within its territory of the natural habitat types and the habitats of species referred to in paragraph 1. To that effect each Member State shall designate, in accordance with Article 4, sites as special areas of conservation taking account of the objectives set out in paragraph 1.

art.4, 1st paragraph. On the basis of the criteria set out in Annex III (Stage 1) and relevant scientific information, each Member State shall propose a list of sites indicating which natural habitat types in Annex I and which species in Annex II that are native to its territory the sites host. For animal species ranging over wide areas these sites shall correspond to the places within the natural range of such species which present the physical or biological factors essential to their life and reproduction. For aquatic species which range over wide areas, such sites will be proposed only where there is a clearly identifiable area representing the physical and biological factors essential to their life and reproduction. Where appropriate, Member States shall propose adaptation of the list in the light of the results of the surveillance referred to in Article 11. [...]

2nd paragraph.[...] Member States whose sites hosting one or more priority natural habitat types and priority species represent more than 5 % of their national territory may, in agreement with the Commission, request that the criteria listed in Annex III (Stage 2) be applied more flexibly in selecting all the sites of Community importance in their territory.[...]

Art. 6, 4th paragraph. If, in spite of a negative assessment of the implications for the site and in the absence of alternative solutions, a plan or project must nevertheless be carried out for imperative reasons of overriding public interest, including those of a social or economic nature, the Member State shall take all compensatory measures necessary to ensure that the overall coherence of Natura 2000 is protected. It shall inform the Commission of the compensatory measures adopted.

Art. 16. Provided that there is no satisfactory alternative and the derogation is not detrimental to the maintenance of the populations of the species concerned at a favourable conservation status in their natural range, Member States may derogate from the provisions of Articles 12, 13, 14 and 15 (a) and (b):[...]

- in the interests of public health and public safety, or for other imperative reasons of overriding public interest, including those of a social or economic nature and beneficial consequences of primary importance for the environment;

[2] Art.4, 1st paragraph. The species mentioned in annex 1 shall be the subject of special conservation measures concerning their habitat in order to ensure their survival and reproduction in their area of distribution. [...]

Trends and variations in population levels shall be taken into account as a background for evaluations. Member states shall classify in particular the most suitable territories in number and size as special protection areas for the conservation of these species, taking into account their protection requirements in the geographical sea and land area where this directive applies.

[3] Directive 92/43 Habitats, art. 2, 2nd paragraph; Directive 79/409 Birds, art. 3, 2nd paragraph, letter c.

*

An engineered liner is included in the design of the Tailings Management Facility (TMF) basin to be protective of groundwater. Specifically, the Roşia Montană Tailings Management Facility (TMF or “the facility”) has been designed to be compliant with the EU Groundwater Directive (80/68/EEC), transposed as Romanian GD 351/2005. The TMF is also designed for compliance with the EU Mine Waste Directive (2006/21/EC) as required by the Terms of Reference established by the MEWM in May, 2005. The following paragraphs provide a discussion of how the facility is compliant with the directives.

The TMF is composed of a series of individual components including:

- the tailings impoundment;
- the tailings dam;
- the secondary seepage collection pond;
- the secondary containment dam; and
- the groundwater monitoring wells/extraction wells located downstream of the Secondary Containment dam.

All of these components are integral parts of the facility and necessary for the facility to perform as designed.

The directives indicated above require that the TMF design be protective of groundwater. For the Roşia Montană project (RMP), this requirement is addressed by consideration of the favorable geology (low permeability shales underlying the TMF impoundment, the TMF dam, and the Secondary Containment dam) and the proposed installation of a low-permeability (1×10^{-6} cm/sec) recompacted soil liner beneath the TMF basin. Please see Chapter 2 of EIA Plan F, “The Tailings Facility Management Plan” for more information.

The proposed low permeability soil liner will be fully compliant with Best Available Techniques (BAT) as defined by EU Directive 96/61 (IPPC) and EU Mine Waste Directive. Additional design features that are included in the design to be protective of groundwater include:

- A low permeability (1×10^{-6} cm/sec) cut off wall within the foundation of the starter dam to control seepage;
- A low permeability (1×10^{-6} cm/sec) core in the starter dam to control seepage;
- A seepage collection dam and pond below the toe of the tailings dam to collect and contain any seepage that does extend beyond the dam centerline,
- A series of monitoring wells, below the toe of the secondary containment dam; to monitor seepage and ensure compliance, before the waste facility limit.

In addition to the design components noted above specific operational requirements will be implemented to be protective of human health and the environment. In the extremely unlikely case that impacted water is detected in the monitoring wells below the secondary containment dam, they will be converted to pumping wells and will be used to extract the impacted water and pump it into the reclaim pond where it will be incorporated into the RMP processing plant water supply system, until the compliance is reestablish.

*

Please consider that the provisions of annex no. 2 to the Government Decision no. 349/2005 on the storing of the wastes, for the verification of the location, regarding *„the positioning in report to the existing or planned populated areas, the protection distance to the warehouse body must be of at least 1,000 meters for the non-dangerous and dangerous wastes deposits”*, do not apply in case of the mining wastes.

The Ministry of Environment and Waters Management, by the Hazardous Chemical Substances and Wastes Management Direction, requested the project titleholder, by the Guidelines sent with a view to the performance of the evaluation of the environmental impact, according to the provisions of the Order of the Minister of Waters and Environmental Protection no. 860/2002 on the environmental impact assessment and environmental approval issuance Procedure, that this project “must be in compliance with the provisions of the new CE Directive on the management of the wastes from the extractive industry”.

To this end, we underline that the Directive no. 2006/21/EC referring to the management of the wastes from the extractive industry provides, at art. 2 (4), that the wastes falling under this directive are exempted from the provisions of the Directive 1999/31/EC on the wastes storing, implemented in the national legislation by GD no. 349/2995. Consequently, the provisions of the Directive 1999/31/EC do not apply to the Roşia Montană project and therefore, neither the provisions of GD no. 349/2005 are applicable. The Directive on the extractive wastes contains provisions and conditions specific in regard of the storing of this type of wastes, and which are applied with priority in report to the regulations already in existence on wastes storing.

*

Detailed financial guarantees are in place, in the form of the Environmental Financial Guarantee (“EFG”), which require Roşia Montană Gold Corporation (“RMGC”) to maintain adequate funds for environmental cleanup. The EFG is updated annually and will always reflect the costs associated with reclamation. The current projected closure cost for Roşia Montană is US \$76 million, which is based on the mine operating for its full 16-year lifespan.

The EFG is governed by the Mining Law (no. 85/2003) and the National Agency for Mineral Resources instructions and Mining Law Enforcement Norms (no. 1208/2003).

Two directives issued by the European Union also impact the EFG: the Mine Waste Directive (“MWD”) and the Environmental Liability Directive (“ELD”).

The Mine Waste Directive aims to ensure that coverage is available for 1) all the obligations connected to the permit granted for the disposal of waste material resulting from mining activities and 2) all of the costs related to the rehabilitation of the land affected by a waste facility. The Environmental Liability Directive regulates the remedies, and measures to be taken by the environmental authorities, in the event of environmental damage created by mining operations, with the goal of ensuring adequate financial resources are available from the operators for environmental cleanup efforts. While these directives have yet to be transposed by the Romanian Government, the deadlines for implementing their enforcement mechanisms are 30 April 2007 (ELD) and 1 May 2008 (MWD) – thus before operations are scheduled to begin at Roşia Montană.

RMGC has already begun the process of complying with these directives, and once their implementation instruments are enacted by the Romanian Government, we will be in full compliance.

Each EFG will follow detailed guidelines generated by the World Bank and the International Council on Mining and Metals.

The annual updates will be completed by independent experts, carried out in consultation with the NAMR, as the Governmental authority competent in mining activities field. These updates will ensure that in the unlikely event of early closure of the project, at any point in time, each EFG will always reflect the costs associated with reclamation. (These annual updates will result in an estimate that exceeds our current US \$76 million costs of closure, because some reclamation activity is incorporated into the routine operations of the mine.)

A number of different financial instruments are available to ensure that RMGC is capable of covering all of the expected closure costs. These instruments, which will be held in protected accounts at the Romanian state disposal, include:

- Cash deposit ;
- Trust funds ;
- Letter of credit ;
- Surety bonds ;
- Insurance policy.

Under the terms of this guarantee, the Romanian government will have no financial liability in connection with the rehabilitation of the Roşia Montană project.
